



Features:

- 21.5" Industrial-grade display with PCAP multi-touch
- Intel® Bay Trail J1900 2.0GHz Processor
- 4G DDR3L RAM, Up to 8GB
- 6*USB、2*RS232、1*HD、1*VGA
- 1*HD、1*VGA
- Fanless design, IP65-rated front panel
- 1* Realtek RTL8111H Gigabit Ethernet, support Wake on LAN/PXE

Specifications:

System Hardware

CPU	Intel® Bay Trail J1900 Quad-core Processor	Memory	4G DDR3L, Up to 8GB
Watchdog	Support hardware reset function (256 levels, 0~255 seconds)	Storage	MSATA: 128GB, up to 512GB

Display

LCD Type	21.5" TFT-LCD	Luminance	250 cd/m ²
Touchscreen Type	21.5" capacitive touch screen	Contrast Ratio	1000: 1
Max. Resolution	1920*1080		

OS

OS	Windows7/10、Linux
----	-------------------

I/O Ports

USB	5*USB2.0 +1*USB3.0	Video	1*HD, 1*VGA
Serial port	2*RS232, 1*RS485 Optional	GPIO	1*GPIO(4In/4Out Optional)
LAN	1* RJ45 Gigabit Ethernet	Expansion Slot	1*Mini PCIe(WiFi/BT/3G/4G Optional)
Audio	1*Line-out, 1*Mic-in	SIM Card	1*Built-in SIM card holder

Power

Power Supply	12V DC input (12/5A power adapter; 9-36V DC IN optional)
--------------	----------------------------------------------------------

Environment

Operating Temp.	-10°C~60°C	Reliability	MTBF≥30000h; MTTR≤0.5h
Storage Temp.	-20°C~70°C	Shock Protection	10G/11ms
Humidity	95% @40°C, non-condensing	Vibration Protection	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g acceleration
IP Rating	Front panel IP65		

Mechanical

Dimension (LxWxH)	543*334.4*56.2mm	Mounting	VESA mounting: 100*100mm Embedded installation: 523*314.4mm
Weight	8.31kg/9.85kg(N.W./G.W.)		
Color	Black/Silver		

Dimensions:

